

Valves for manometers.

Technical data

Shut-off valve 8NVFG

- PN 400 DN5
- female/male connections
- non-rotating plug

Technical data

Input/output: G $\frac{1}{2}$ "
Max pressure: 40MPa
Air bleeding: none

Components

Housing: SS316
Knob: SS304
Sealing: teflon
Other: SS316
Housing dimensions: 32x32x68mm



Temperature	Material: steel
room	60 MPa
260°C	40 MPa
540°C	15 MPa

3-way valve N542.39...

- 3-way block with non-rotating plug
- direct mounting, transmitter acc. to the DIN 19 213/IEC
- PN 420 DN 5
- sealing PTFE 200°C
- special execution up to 400°

Material	Input	Output	Serial no.
St. C22.8	½NPT	contacts	N 542.39.181.01
St. 1.4401	½NPT	contacts	N 542.39.481.01



5-way valve N542.48...

- 5-way block with non-rotating plug
- direct mounting, transmitter acc. to the DIN 19 213/IEC
- PN 420 DN 5
- sealing PTFE 200°C
- special execution up to 400°

Material	Input	Output	Serial no.
St. C22.8	½NPT	contacts	N 542.48.180.01
St. 1.4401	½NPT	contacts	N 542.48.480.01

