

Connection heads are integral elements of temperature sensors, available also as separate components. They are made primarily of aluminium alloys, but stainless steel, polyamide or noryl heads are also available. Wide range of connection heads allows head selection according to client requirements and application specifications.

Specification

NAA

- body and cover material: aluminium alloy
- coating: polyester lacquer
- operating temperature:
 - 40÷100°C oil-proof rubber seal
 - 40÷150°C silicone seal
- inner dimensions [mm]: $\varnothing 42 \times 28$
- protection tube entry: M24x1,5



DAA

- body and cover material: aluminium alloy
- coating: creodur lacquer
- operating temperature:
 - 40÷100°C oil-proof rubber seal
 - 40÷150°C silicone seal
- inner dimensions [mm]: $\varnothing 56 \times 22$ or $\varnothing 42 \times 40$
- protection tube entry: $\varnothing 22,5$; $\varnothing 32,5$ mm



DANAWwin

- cover with window
- coating: polyester lacquer
- operating temperature:
 - 40÷80°C
- connection head height [mm]: ~114
- protection tube entry: M10x1



DAAW

- body and cover material: aluminium alloy
- coating: polyester lacquer
- operating temperature:
 - 40÷100°C oil-proof rubber seal
 - 40÷150°C silicone seal
- connection head height [mm]: 127
- protection tube entry [mm]: $\varnothing 22,5$; 32,5



DANAW

- body and cover material: aluminium alloy
- coating: creodur lacquer
- operating temperature:
 - 40÷100°C oil-proof rubber seal
 - 40÷150°C silicone seal
- connection head height [mm]: 114
- protection tube entry: M24x1,5

